



# MS852B

## Bluetooth<sup>®</sup> 2D Imager Scanner



Combining mobility wireless design and 2D scanning performance in one scanner, the unitech MS852B wireless scanner delivers the simple way to do the inventory control faster and efficiency for business solutions from warehousing, manufacturing, logistics to general purpose retail scanning.

### Move without Restrictions

Featuring 2D scanning technology, the MS852B has the ability to capture most 1D / 2D barcodes on mobile screens, even damaged or poorly printed barcodes. Moreover, the MS852B supports Bluetooth<sup>®</sup> dual mode technology (Bluetooth<sup>®</sup> LE V4.2 & Bluetooth<sup>®</sup> 2.1+EDR, Class 1) to give you the freedom and bring your business the flexibility. It is compatible with any smartphone, tablet, or computer—the MS852B pairs easily to any mobile device or PC. Besides, it allows users to transmit data to the host from up to 100 meters from the base. When it is out of range, the MS852B barcode scanner can store 590,000 codes in memory and upload to your devices at your own convenience.

### User-Friendly with Cradle Accessory

This MS852B+ wireless scanner has a cradle accessory that supports auto Bluetooth<sup>®</sup> pairing and it has the ability to switch between trigger or presentation mode automatically.

### Compact but durable

Built for all day use, the MS852B is built in a lithium-ion battery can be replaced easily. It has a long life battery life up to 40 hours per battery charge. While sustaining a 2.1 meter drop to concrete, MS852B incorporated with IP42 rugged design for protection against dust and moisture. Moreover, the built-in long lifecycle trigger of 10 million times guarantees a continuous productivity for best reliability. This scanner can be used in the most practical way depending on the scanning task in various solutions in retail, warehousing, manufacturing, logistics.

### Features

- Support most 1D / 2D barcode on mobile screens, even damaged or poorly printed barcodes
- Support Bluetooth<sup>®</sup> dual mode technology (Bluetooth<sup>®</sup> LE V4.2 & Bluetooth<sup>®</sup> 2.1+EDR, Class 1)
- Wireless transmission range up to 100m in the line of open sight
- Long battery life up to 40 hours per a fully charged battery
- Durable design : IP42 and 2.1m drop spec
- Auto Bluetooth pairing / auto switch between trigger & presentation mode with cradle

**unitech**  
because we care



# MS852B

## Specifications

### Optical & Performance

Sensor	CMOS sensor with 640 x 400 pixel
Aiming Element	610nm
Illumination	Hyper Red 660nm
Imager Field of View	10000 ft. candles (107,639 lux)
Skew Angle	±60°
Pitch Angle Sensor	±60°
Roll Angle	0 - 360°
Optical Resolution	5.0 mil (Code 39), 6.6 mil (PDF417)
Printing Contrast Scale	Minimum 20%
Depth of Field (DOF PCS=80%)	SYMBOLGY / X-DIM TYPICAL RANGE* Near Far
	5 mil Code 39 2.0 in / 5.1 cm 6.4 in / 16.2 cm
	5 mil Code 128 2.5 in / 6.3 cm 5.0 in / 12.7 cm
	6.6 mil PDF417 2.5 in / 6.3 cm 6.3 in / 16.0 cm
	10 mil PDF417 1.8 in / 4.5 cm* 9.0 in / 22.8 cm
	13 mil 100% UPC 2.0 in / 5.0 cm* 12.5 in / 31.7 cm
	20 mil Code 39 2.0 in / 5.0 cm* 19.5 in / 49.5 cm
	20 mil Data Matrix 1.5 in / 3.8 cm 13.5 in / 34.3 cm
	20 mil QR Code 1.5 in / 3.8 cm 11.0 in / 27.9 cm

### Communication

Radio	Bluetooth® LE V4.2 Bluetooth® 2.1+EDR, Class1 Dual mode
Wireless Coverage	100m ( line of sight)
Interface/ Profile	Serial Port and HID profiles
Host Interface supported	USB, RS232

### Mechanical

Scanner Dimension	87.8 L x 71.6 W x 177.7 H (mm)
Scanner Weight	213g (without cradle)
Trigger Switch Life	10 million times
Cradle Dimension	120.6 L x 88.7 W x 86.0 H (mm)

### Symbologies

1D	All major symbologies and PDF417
2D	2D :QR Code, Data Matrix, Aztec Code, PDF417, Macro PDF417, Micro PDF417, MaxiCode, Coda block A, Codablock F, GS1Composite, Han Xin Code
	Postal: Australian Post, British Post, Canadian Pos, InfoMail, Intelligent Mail Bar Code, Japanese Post, KIX (Netherlands) Post, GS1 Composite, Korea Post, Planet Code, Postal, Postnet

### Electrical

Indicator	LED & Beeper & Vibrator
Battery Type	Rechargeable and replaceable battery pack.
Battery Capacity	2850mAh
Battery Charging time	<6.5 hours
Operating Time	>40 hours

### Environmental

ESD Protection	Functional after 8K Contact and 15K Air
Mechanical Shock	2.1M onto concrete (scanner only)
Operating Temperature	-10°C to 50°C (14°F to 122°F)
Storage Temperature	-40°C to +70°C (-40°F to +158°F)
Relative Humidity	95% non-condensing
IP Rating	IP42

### Accessories

Cradle
Interface cable
Battery pack

### Package Contents

MS852B Scanner with battery
Cradle
Interface cable

### Regulatory Approvals

CE, FCC, BSMI, VCCI, NCC, TELEC, BQB



#### Headquarters

Taipei, Taiwan  
<http://www.ute.com> e-mail: [info@hq.ute.com](mailto:info@hq.ute.com)

#### unitech America

Los Angeles  
<http://us.ute.com> e-mail: [info@us.ute.com](mailto:info@us.ute.com)  
<http://can.ute.com> [info@can.ute.com](mailto:info@can.ute.com)

Mexico  
<http://latin.ute.com> e-mail: [info@latin.ute.com](mailto:info@latin.ute.com)

#### unitech Asia Pacific & Middle East

Taipei  
<http://apac.ute.com> [info@apac.ute.com](mailto:info@apac.ute.com) / [info@india.ute.com](mailto:info@india.ute.com)  
<http://mideast.ute.com> [info@mideast.ute.com](mailto:info@mideast.ute.com)

#### unitech Europe

Tilburg / Netherlands  
<http://eu.ute.com> e-mail: [info@eu.ute.com](mailto:info@eu.ute.com)

#### unitech Japan

Tokyo  
<http://jp.ute.com> e-mail: [info@jp.ute.com](mailto:info@jp.ute.com)

#### unitech Greater China

Beijing, Shanghai, Guang Zhou, Xiamen  
<http://cn.ute.com> [info@cn.ute.com](mailto:info@cn.ute.com)  
Taipei <http://tw.ute.com> [info@tw.ute.com](mailto:info@tw.ute.com)

